

One Line / 15 Character Electronic Message Center



The Alpha® 215 Series indoor LED displays are message centers designed for light industrial, commercial and office use. They quickly display large amounts of information in 8 colors and 3 rainbow effects (red-only versions are also available). These message centers are among the brightest and sharpest indoor LED displays available.

Pixel Size (Diameter):	0.2" (.05 cm)
Pixel (LED) Color:	Each dot can be red, green, or amber
Center-to-Center Pixel Spacing (Pitch):	0.3" (0.8 cm)
Character Size:	2.1" (5.3cm)
Character Set:	International Character Set, Black (sans serif), decorative (serif), upper/lower case, slim, wide, double wide, and shadowing
Memory Retention:	One month typical
Message Capacity:	81 different messages can be stored and displayed
Message Operating Modes:	<ul style="list-style-type: none"> • 26, including Automode™, Hold, Roll (6 directions), Rotate, Sparkle-On, Twinkle, Interlock, Wipe (6 directions), Flash, Scroll, Snow, Starburst, Spray-on, Switch, Condensed Rotate and Cycle Color • Continuous message entry with automatic centering in any mode • User programmable logos and graphics • Five hold speeds
Built-In Animations:	Cherry Bomb Exploding, Don't Drink and Drive, Fireworks, Slot Machine, No Smoking, Fish, Welcome and Thank You, Trumpet and News Flash
Real-Time Clock:	Date and time, 12 or 24 hour format, maintains accurate time without power for up to 30 days typical.
Computer Interface:	RS232 and RS485 (multi-drop networking for up to 255 displays) Optional Ethernet LAN Interface
Power:	Input: 5A, 35W, 7 VAC. 120VAC or 230VAC adapter available
Maximum Power Cord Length:	10ft. (3m)
Keyboard:	Handheld, IR remote
Case Material:	Molded plastic
Limited Warranty:	One-year parts and labor, factory servicing
Agency Approvals:	<ul style="list-style-type: none"> • 120 VAC Model: Power supply has UL/CSA listing. • 230 VAC Models: Complies with EN 60950: 1992 (Europe). • FCC Part 15 Class A • CE Marked
Operating Temperature:	32° to 120° F, 0° to 49° C
Humidity Range:	0% to 95% non-condensing
Mounting:	Hardware to accommodate ceiling or wall mounting

SIZE	215C/215R
Case Dimensions LxDxH:	28.9" x 2.1" x 4.5" 73.4cm x 5.3 x 11.4
Approximate Weight:	6.25lbs. (2.13kg.)
Display Dimensions:	27" x 2.1" 68.6cm x 5.3
Display Array:	90 x 7 pixels
Characters Displayed per line: One-line	15 characters
Display Memory:	6,000 Characters (Alpha 215C) 7,000 characters (Alpha 215R)